

PT-201 DDC/BAS PROGRAMMER TRAINING UNIT

The PT-201 is designed specifically for training DDC/BAS programmers who work with programmable unitary controllers. Graphical object oriented programming is presented using the non-proprietary, open-licensed Sedona Framework®.

Specifications

Power Requirements: 50W; 120VAC; 60Hz

Operating Temperature: 55°F to 85°F

Storage Temperature: 10°F to 110°F

Relative Humidity: 10 to 95% RH non-condensing

Mounting: 5/16" carriage bolts (2) optional

Shipping Weight: 20 lbs (not including workbooks)

Dimensions: 18.5"W x 14"H x 7"D (w/cover)

Features

- Programmable Sedona 20 point unitary controller with BACnet IP, and web interface
- Instrument panel with Input/Output components and 24VAC posts
- Belimo 2-10VDC Actuator with 2-10VDC position feedback
- Relay with HOA switch
- 0-20VDC Digital meter
- 5 port Ethernet switch 10/100mpbs
- Banana plug jumper kit with storage pouch

The PT-201 DDC/BAS Programming system can be purchased in two versions:

PT-201-Bc20 – Contemporary Controls BAScontrol20 controller, BAS Toolkit software, Intro to Sedona Course Curriculum (USB Drive). Pre-wired Banana Test Leads. Full 1 yr. warranty.

PT-201-DIN – DIN rail mount (No controller included), BAS Toolkit, Banana Test Lead Kit. Limited 1yr. warranty. No curriculum included.



Shipping Weight: 20 lbs.

Shipping Dimensions: 24" L x 18" W x 10" H